



כשבית פוגש טכנולוגיה

HW-C3-W

מצלמת חוץ אלחוטית מוגנת מים 2 מ"פ ומסתובבת 360



תכונות המוצר

- * Advanced P2P technology, easy to install and preview;
- * H.264 main profile video compression standard;
- * Full HD 1080P video technology;
- * Built-in IR LEDs to capture video in low-light environments;
- * Built-in microphone & speaker, support two-way audio intercom;
- * Multi-way to Achieve Internet Connection - Ethernet, WiFi or AP
- * Support alert push, image or message can be sent to your smartphone;
- * Support local and remote recording & playback;
- * One TF card slot storage, max. up to 64G;

Full HD
1080



Night Vision



Motion Detection



2-way Audio



Cloud Storage



Remote Control

מפרט טכני

| Camera | |
|-------------------|--|
| Image Sensor | 1/2.7" Progressive CMOS |
| Min. Illumination | Color 0.1Lux, black and white 0.01 Lux |
| Max. Resolution | 1920x1080 |
| Lens Type | Fixed-focal |
| Focal Length | f = 3.6 mm |
| View Angle | 85° |
| Pan & Tilt Range | Pan 355°; Tilt 155° |
| Day & Night | IR cut filter with auto switch |
| Max. IR Range | 10m / 33ft |
| Video | |
| Video Standard | PAL / NTSC |
| Compression | H.264 High profile |
| Max. Frame Rate | 15fps (1920x1080) |
| Max. Streams | 2 simultaneous streams |
| Video Streaming | Adjustable resolution, quality and bitrate, Configurable video cropping for bandwidth saving |
| Image Settings | Brightness, saturation, sharpness, contrast are adjustable |

| Video Storage | |
|---------------------------|---|
| On-board Storage | Built-in micro SD slot, MAX. up to 64 GB (not incl.) |
| | Cloud Storage |
| Audio | |
| Compression | AAC; G.711U |
| 2-Way Audio | Support |
| Input | Built-in microphone |
| Output | Built-in speaker |
| Environment Noise Filter | Support |
| Network | |
| Protocols | RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP, etc. |
| Wireless Standards | IEEE802.11/b/g/n |
| Frequency Range | 2.4 GHz |
| AP Hotspot | Support |
| Security Protection | Password Encryption |
| Alarm and Event | |
| Alarm Triggers | Video motion detection, manual trigger, periodical trigger, system boot, recording notification |
| Alarm Events | Alarm bell notification, push notification, manually taken snapshots and video clips are saved to mobile device |
| System Integration | |
| Operation system | Embedded Linux OS |
| Supported Platform | iOS & Android |
| Physical | |
| Ethernet Interface | RJ45, 10M / 100M Adaptive Ethernet port |
| Power Supply | DC 5 V \pm 10 %; 1A |
| Power Consumption | Max. 3W |
| Operating Conditions | -10 °C to 60°C (14 °F to 140 °F); 10% ~ 90% non-condensing RH |
| Material | ABS Plastic Housing |
| Dimensions | 170 x 110 x 150 mm |
| IP Rating | IP66 |

